

DS-K1107AMK Card Reader



- Equipped with the 32-bit high-speed processor
- RS-485 and Wiegand (W26/W34) protocol, and OSDP protocol
- Build-in M1 card reading module (Frequency: 13.56MHz).
- Supports tampering alarm
- Built-in buzzer for identifying the reading status
- Online upgrade function
- Watchdog design for repairing itself in case that exception occurs, to ensure the long service life of the reader

**Card Reader*

▪ Specification

| Interface | |
|------------------------|--|
| TAMPER | 1 |
| RS-485 | 1 |
| Wiegand | 1 (set via DIP switch) |
| Authentication | |
| Card reading frequency | 13.56 MHz |
| General | |
| Power supply | 12 VDC |
| Power consumption | ≤ 2 W |
| Working temperature | -20 °C to 65 °C (-4 °F to 149 °F) |
| Working humidity | 10% to 90% (no condensing) |
| Dimensions | 115 mm × 44 mm × 22 mm (4.53" × 1.73" × 0.87") |
| Installation | Wall mounting with screws; Do not support gang box |
| Weight | Gross weight: 0.25 kg (0.55 lb) Net weight: 0.16 kg (0.35 lb) |
| Keypad | 12 Keys (0 to 9, *, #) |
| Buzzer | Support |

▪ Available Model

DS-K1107AMK

Headquarters

No.555 Qianmo Road, Binjiang District,
Hangzhou 310051, China
T +86-571-8807-5998
www.hikvision.com



Follow us on social media to get the latest product and solution information.



Hikvision



HikvisionHQ



HikvisionHQ



Hikvision_Global



Hikvision
Corporate Channel



hikvisionhq